



Specifications

Input: GV-600 BNC: BNC X 4

GV-600 D-Type: DB15 X 2

Video inputs: 1, 2, 4, 6, 8, 10, 12, 14, 16 Cameras

Audio Inputs: 1 Channel

Total Recording Speed: The 320 X 240 resolution
30 fps (NTSC), 25 fps (PAL)

Image: 30 fps (NTSC), 25 fps (PAL)

Video Resolution - NTSC / PAL: Full D1, Half D1, CIF

Compression format: Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2

GV-A16 Support: Yes

GV-NET Card Support: Yes

GV-NET/IO Card Support: Yes

Dimensions (W x H): GV-600 BNC: 144 x 89 (mm) / 5.67 x 3.50 (in)

GV-600 D-Type: 144 x 89 (mm) / 5.67 x 3.50 (in)

Installation manual: Installing two cards

Note: GV-600 is currently not compatible with VIA series and ATI series chipset motherboard,
and 64-bit Windows operating system

Minimum requirements for a card

OS Supported

Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista

(does not support 64-bit version of Windows)

CPU: Pentium 4-2.0 GHz

RAM: Windows 2000 / XP: 2 x 512 MB Dual Channels

Windows Vista / Server 2003: 2 x 1 GB Dual Channels

HDD: 80 GB

VGA: ATI Radeon X600, NVIDIA 6200

DirectX: 9.0c

Minimum requirements for two cards

OS Supported

Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista

(does not support 64-bit version of Windows)

CPU: Pentium 4-2.6 GHz with Hyper-threading

RAM: 2 x 1 GB Dual Channels

HDD: 160 GB

VGA: ATI Radeon X600, NVIDIA 6200

DirectX: 9.0c